



F&W—Áá|Ááá~• [!^ÁÔæ}æ|^Á&^}c|æ|^Áá^||æÁ*æ { { æÁRÉÁÁ
 QÁ á~^Á , [[~^!Á áæ|Á áææ { ^c:[Á ááá FH€ { { Á • [] [Á] [• á : á [] æcáÁ
 •á { { ^c!á&æ { ^}c^Á æáÁ |æcáÁ á^||c~}áæÁ W}áÉÛÁ á}Á
 & []~á*~!æ:á []^Á áOCE]] [[ác [ÉÁ Ö!æ:á^Á æÁ ~^•cæÁ c^&}á&æÉÁ •áÁ
 [ccá^}^Á ááÁ~æcc [Á ~}Á ^~^ccáç [Á Á~}á& [Á ~}c [Á ááÁ ^ { á••á []^ÁÁ
 •~||æÁá}c^!æÁ*æ { { æÁááá~!^~^} : ^ÉÁ!^•^!çæ}á [Á { ~•á&æ|áæÁ
 }æc~!æ|^: :æÁ^Á!á]! [á~:á []^Ác!ááá { ^}•á []æ|^ÉÁ

Specifiche Tecniche

Design Tre Vie bass reflex
Drive units Uni-Q Driver Array:
 HF: 25mm
 Cupola in Alluminio Ventilato
 MF: 125mm in Alluminio
 Bass Driver:
 2 x 130mm
 Alluminio Ibrido

Frequenza di Crossover 400Hz, 2.9kHz
Range di risposta (-6dB) 64Hz - 50kHz
Risposta tipica in ambiente (-6dB) 49Hz

Üá• []•cæáá}ÁØ!^~^} : æÁç!HáÓD 74Hz - 28kHz
ÁÖá•c [!•á []^ÁCE! { []á&æ <0.3% 120Hz - 20kHz
T æ••á { æÁ!^••á []^ÁÛÚŠÁ 110dB
CE []|á~á&æ:á []^Á& []•á*|áæcæ 15 - 200W

Q []^á^} : æÁP [{ á}æ|^Á 8Ω (min.3.2Ω)
Ú^}•áá|áæÁçGÉ!HXDF { D 87dB
Ú^• [16.9 kg (37.3 lbs.)
Öá { ^}•á []áçCEÁçÁŠÁçÁÚD 175 x 550 x 308.5 mm

Øá}ác~!^ Black Gloss / White Gloss / Walnut

